



FLOORS

# PREMIUM HERRINGBONE

## *Facts*

<b>Use Class</b>	EN 16511	33
<b>Thickness</b>	EN 17539	6 mm (5+1 mm)
<b>Width</b>	EN 17539	146 mm
<b>Length</b>	EN 17539	730 mm
<b>Panels per Box</b>		16
<b>Box Content</b>		1.705 m <sup>2</sup>
<b>Box Weight</b>		17.88 kg
<b>Profile</b>		UNIZIP® One Panel System
<b>Bevel</b>		Microbevel 4-sided
<b>Wearlayer</b>	ISO 24340:2006 (E)	0.55 mm
<b>Surface</b>		EiR/Synchronpore (Gloss level 3-5)
<b>Abrasion Class</b>		AC 5
<b>Reaction to Fire (CE)</b>	EN 13501-1	B1
<b>Thermal Conductivity</b>	EN 12667	0.111 W/m·K
<b>Underfloor Heating Suitability</b>		✓
<b>Slip Resistance</b>		R9
<b>Abrasion Resistance</b>		≥ 5,000 r
<b>Locking Strength</b>	ISO 24334	≥ 3.5 kN/m
<b>Microscratch Resistance</b>	EN 16094	B2
<b>Dimensional Stability</b>	EN ISO 23999	≤ 0.15 %
<b>Impact Sound Insulation</b>		1 mm IXPE, 10X
<b>Impact Sound Improvement</b>	ISO 10140-3	20 dB
<b>Formaldehyde/VOC Emissions Free</b>		✓
<b>Phthalat Free</b>		✓